Air Conditioning

Product Information

MFZ-KJ35VE Inverter Heat Pump Floor Mounted System

Making a World of Difference



The MFZ-KJ series is extremely versatile and is designed for wall attached installation at floor level.

Key Features

- Swing Vane Mode with Auto Vane Shutter
- Infra-red remote controller
- Econo Cool allows set temperature to be raised by 2°C without any loss of comfort and a 20% gain in energy efficiency
- Auto-Restart
- Quiet operation
- Auto-Changeover
- Hot Start draught prevention
- Anti-Allergy Enzyme filter artificial enzymecatalyst on the filament catches allergens
- Replace Technology available



Air Conditioning | Heating Ventilation | Controls



Product Information

Air Conditioning

MFZ-KJ35VE Inverter Heat Pump Floor Mounted System

Making a World of Difference

MFZ-KJ - INDOOR UNIT		MFZ-KJ35VE
CAPACITY (kW)	Heating (nominal)	4.3 (1.2-5.5)
	Cooling (nominal)	3.5 (0.5-3.7)
	Heating (UK)	3.3 (0.75-5.15)
	Cooling (UK)	3.47 (0.9-3.85)
SHF (nominal & UK)		0.65
COP / EER (nominal)		3.91 / 3.72
SCOP / SEER (BS EN14825)		4.4 / 7.8
ErP ENERGY EFFICIENCY CLASS Heating/Cooling		A+ / A++
AIRFLOW (I/s)	Heating/Cooling - Lo-Mi-Hi-SupHi	87-103-130-158 / 83-102-123-152
PIPE SIZE mm (in)	Gas	9.52 (3/8")
	Liquid	6.35 (1/4")
SOUND PRESSURE LEVEL (dBA) Heating/Cooling - Lo-Mi-Hi-SupHi		19-25-30-35-41 / 20-25-30-35-39
SOUND POWER LEVEL (dBA)		50
DIMENSIONS (mm)	Width x Depth x Height	750 x 215 x 600
WEIGHT (kg)		15
ELECTRICAL SUPPLY		Fed by Outdoor Unit
FUSE RATING (BS88) - HRC (A)		6
INTERCONNECTING CABLE No. CORES		4

DIMENSIONS		
750 656 100 D 100	More than 1000mm 00 99	28 215 70 88 Air out 148 Sensor hole Air in 104 131 153
		730

MUFZ-KJ - OUTDOOR UNIT	MUFZ-KJ35VE
SOUND PRESSURE LEVEL (dBA) Heating/Cooling	51 / 47
SOUND POWER LEVEL (dBA) Cooling	60
WEIGHT (kg)	37
DIMENSIONS (mm) Width x Depth x Height	800 x 285 x 550
ELECTRICAL SUPPLY	220-240v, 50Hz
PHASE	Single
SYSTEM POWER INPUT (kW) Heating/Cooling (nominal)	1.11 / 0.94
Heating/Cooling (UK)	1.01 / 0.74
STARTING CURRENT (A)	5.1
SYSTEM RUNNING CURRENT (A) Heating/Cooling [MAX]	5.1 / 4.2 [9.4]
FUSE RATING (BS88) - HRC (A)	10
MAINS CABLE No. CORES	3
MAX PIPE LENGTH (m)	20
MAX HEIGHT DIFFERENCE (m)	12
CHARGE R410A (kg) - 7m	1.05







Telephone: 01707 282880

email: air.conditioning@meuk.mee.com web: www.airconditioning.mitsubishielectric.co.uk

UNITED KINGDOM Mitsubishi Electric Europe Living Environmental Systems Division Travellers Lane, Hatfield, Hertfordshire, AL10 8XB, England General Enquiries Telephone: 01707 282880 Fax: 01707 278881 IRELAND Mitsubishi Electric Europe Westgate Business Park, Ballymount, Dublin 24, Ireland

Country of origin: United Kingdom – Japan – Thalland – Malaysia. (Mitsubish) Electric Europe 2015. Mitsubish) and Mitsubishi Electric are trademarks of Mitsubishi Electric Europe B.V. The company reserves the right to nake any variation in technical specification to the equipment described, or to withdraw or replace products without prior notification or public amountement. Mitsubishi Electric is constantly developing and improving its products. All descriptions, illustrations, drawings and specifications in this publication present only general particulars and shall not form part of any contract. All goods are supplied subject to the Company's General Conditions of Sale, a copy of which is available on request. Third-party product and brand remes may be trademarks or registered trademarks of their respective owners.










Telephone: Dublin (01) 419 8800 Fax: Dublin (01) 419 8890 International code: (003531)





Mitsubishi Electric UK's commitment to the environment





